

## AIR ENTRAINING AGENT FOR CONCRETE (ASTM C-260)

### DESCRIPTION

AIR-RIGHT® is a ready-to-use, synthetic air-entraining agent for concrete. AIR-RIGHT® meets the requirements of ASTM C-260, CRD C-13 and AASHTO M-154 specifications for air-entraining agents for concrete.

### ADVANTAGES

Consistent performance	Reduced bleeding and segregation
Economical	Reduced permeability – better water resistance
Smaller bubble sizing	Increased durability
Improved dispersion	Improved workability

### PERFORMANCE

The stable air void system developed using AIR-RIGHT® can be used to obtain freeze/thaw durable concrete in properly proportioned mixes using standard industry practices. AIR-RIGHT® concrete is more resistant to de-icing salts, sulfate attack and corrosive water. Air-entrained concrete reduces bleeding and helps to increase workability of lean/harsh mixes.

### NON-CHLORIDE, NON-CORROSIVE

AIR-RIGHT™ admixture will not initiate or promote corrosion of reinforcing steel embedded in concrete, pre-stressed concrete or concrete placed on galvanized steel floor and roof systems.

### DOSAGE

AIR-RIGHT® is recommended for use at the rate of ½ to 1 ½ oz. per 100 lbs of cement depending upon the application, required strength or desired slump. Test mixes should be performed before use. For additional information, see the quick guide located on the reverse side of this sheet or contact your Great Eastern representative.

### COMPATIBILITY

AIR-RIGHT® should not be mixed with other admixtures prior to addition to concrete.

### PACKAGING

Bulk, totes, 55gallon drums, 5 gallon pails

### PRECAUTIONS

Care should be taken to maintain product above 40°F. Refer to MSDS for chemical properties



P.O. BOX 3015 Phone 1-888-452-9348  
Lakewood, NJ 08701 Fax 732-367-9473

*Technology and Products That Offer Solutions*

NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY.  
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION.

Great Eastern Technologies, L.L.C. warrants its products to be free of manufacturing defects and that they will meet Great Eastern Technologies', L.L.C. current published physical properties when applied in accordance with Great Eastern Technologies', L.L.C. directions and tested in accordance with ASTM and Great Eastern Technologies, L.L.C. standards. There are no other warranties by Great Eastern Technologies, L.L.C. of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with the product. Great Eastern Technologies, L.L.C. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty, whether expressed or implied, including any warranty of merchantability or fitness for a particular purpose or from any other cause whatsoever. Great Eastern Technologies, L.L.C. shall also not be responsible for use of this product in a manner to infringe on any patent held by others.